JF-VS-7116D

16 HDD Storage Server





Features

- Manage platform software professionally
- High-performance processor
- System information real-time backup
- RAID optimization technology
- Multi-functional integration
- ◆ Multi-level server cluster, cascade
- User-friendly operation and maintenance interface
- High-performance streaming data management structure
- Simple open architecture
- Advanced network transmission
- Adapt to a variety of architectures
- Alarm management and video collaboration
- Rich video applications
- ◆ Testing equipment operating status
- Perfect log management
- ◆ CPU Smart FM
- Intelligent fan speed control fine
- Intelligent drive hibernation
- ◆ Remote server configuration
- ♦ Memory self-starting function
- Redundant power supply
- Density chassis design

Dimensions



JF-VS-7116D

16 HDD Storage Server

Specification

Model	VS7116D
Performance	
Video (2Mbps)	200-ch Management +200-ch Recording +100-ch Forwarding
System Parameter	
Main Processor	Intel Xeon quad-core processor
Operating System	Embedded LINUX
Cache	Standard 4GB,(Extension to 32G)
Power Mode	support 1 + 1 redundant power supply
Disk	
Built-in Disk	500G SATA 6.0Gb/s 2.5 inch Built-in Disk*1
Hard Disk Number	SATA Disk (Maximum support single disk 6TB)*16
Disk Installation	Independent disk bracket, hotplug,SATA 3Gb/s,6.0Gb/s
RAID Mode	Hardware level Raid0, 1, 5, 6, 10, 50, JBOD, Support for global and special hot spare parts
External Interface	
Network Interface	Intel Dual Gigabit Ethernet Interface
USB Interface	USB3.0*2;USB2.0*5
Parallel port communication	RS232*1
Display Interface	VGA*1
Alarm	16-ch alarm input,8-ch alarm output
Panel Display	
Button	Power switch, reset button
	Front: power indicator*1, network indicator*2,
LED Indicator	built-in disk indicator*1, built-in fan indicator*1
	Back: network indicator*2, bracket: disk status lights*2
General	
Power Supply	550W 1+1 redundant power supply, support for online replacement
Voltage Input	180~240V,47Hz~63HZ
Working Temperature	Working:5 $^{\circ}$ C \sim 40 $^{\circ}$ C Storage:-20 $^{\circ}$ C \sim 70 $^{\circ}$ C
Working Humidity	Working: 20%~80%RH(No Ice、No Condensation)
	Storage: 5%~95%RH(No Ice、No Condensation)
Case	3U standard
Dimension(mm)	440(width)x133(depth)x650mm(height)
Weight (Disk not included)	20Kg

JF TECH Co.,Ltd.

Headquarters (Hangzhou):

Building 9, Yinhu Innovation Center, Hangzhou, China

Business Center(Shenzhen):

Website:http://www.jftech.com

Tel:+86-0571-23271188

Tel:+86-0755-32898088

A 7th Floor, Block Sakata 5 Avenue and Chong Hing Times Tower Shenzhen All Rights Reserved • Specifications subject to change without notice.