

JF-ADVR-T7104/T7108/T7116

4ch/8ch/16ch Fribrid 720P 1HDD ADVR



Features

- ◆ Support 4ch Real-time Encoding 8ch/16ch 1080N Unreal-time Encoding
- ◆ Support AHD/TVI/CVI/CVBS/IP Self-adaptive
- ◆ HDMI/VGA Simultaneous Video Output
- ◆ Support DHCP,FTP,DNS,DDNS,NTP,UPNP,EMAIL,3G,WIFI
- ◆ Support ONVIF Protocol
- ◆ Support WEB,VMS, MYEYE Platform
- ◆ Support Mobile Phone Monitoring(IOS ,Android)
- ◆ Cloud Services,P2P,Alarm Information Push To Phone
- ◆ Support Multi-Language

Dimensions



JF-ADVR-T7104/T7108/T7116

4ch/8ch/16ch Fribrid 720P 1HDD ADVR

Specification

1 HDD				
Model	JF-ADVR-T7104	JF-ADVR-T7108	JF-ADVR-T7116	
Video				
Encode	4CH*1080N@25fps	8CH*1080N@12fps	16CH*1080N@12fps	
Playback	1CH*1080N@25fps	8CH*1080N@12fps	16CH*1080N@12fps	
Multi-Mode	Analog	4CH*1080N	8CH*1080N	16CH*1080N
	Hybrid	2CH*720P(Analog)+2CH*720P(IP)	4CH*1080N(Analog)+4CH*960P(IP)	8CH*1080N(Analog)+8CH*960P(IP)
	IP	8CH*1080P/8CH*720P	16CH*1080P/9CH*1080P/ 16CH*960P/4CH*5M	8CH*1080P+8CH*960P/16CH*960P /4CH*3M/4CH*5M
Video Compression	H.264			
Audio				
Audio Compression	G.711A			
Interface				
Video Input	4*BNC	8*BNC	16*BNC	
Video Output	1*VGA,1*HDMI			
Audio I/O	4/1		2/1	
Alarm I/O	--			
Ethernet	1*10/100Mbps Ethernet port, RJ45 port			
PTZ Control	1*RS485, Support for multiple PTZ protocol			
USB	2*USB2.0			
Max HDD	1×8TB			
General				
Temperature	0 °C - + 55 °C			
Humidity	10%-90%RH			
Power	12V/2A			
Consumption	<15W(Without HDD)			
Dimension	255(L)* 236mm(W)* 44mm(H)			

JF TECH Co.,Ltd.

Headquarters(Hangzhou):

Building 9, Yinhu Innovation Center, Hangzhou, China

Business Center(Shenzhen):

A 7th Floor, Block Sakata 5 Avenue and Chong Hing Times Tower Shenzhen

All Rights Reserved • Specifications subject to change without notice.

Website:<http://www.jftech.com>

Tel:+86-0571-23271188

Tel:+86-0755-32898088