

JF-ADVR-T8408

8ch Fribrid 4M 1HDD ADVR



Features

- ◆ Up to 5M@6fps,4M@8fps
- ◆ Support XVI/AHD/TVI/CVI/ CVBS/IP Self-adaptive
- ◆ Support Intelligent Functions
- ◆ Support D/A Conversion(Free combination of Analog and IP in pure Analog mode)
- ◆ HDMI/VGA Simultaneous Video Output
- ◆ Support DHCP,FTP,DNS,DDNS,NTP,UPNP,EMAIL,3G,WIFI
- ◆ Support ONVIF Protocol
- ◆ Support WEB,VMS,MYEYE Platform
- ◆ Support Mobile Phone Monitoring(IOS ,Android)
- ◆ Cloud Services,P2P,Alarm Information Push To Phone
- ◆ Support Multi-Language

Dimensions



JF-ADVR-T8408

8ch Fribrid 4M 1HDD ADVR

Specification

1HDD		
Model	JF-ADVR-T8408	
Video		
Encode	8*5M@6fps/8*4M@8fps	
Playback	2*5M@6fps/8*4M@8fps	
Multi-Mode	Analog	8*5M/8*4M/8*1080P
	Hybrid	4*4M(Analog)+4*4M(IP)
		8*4M(Analog)+8*4M(IP)
IP	8*1080P+8*960P/4*3M/4*5M	
Video Compression	H.265/H.265+/H.264/H.264+	
Audio		
Compression	G.711A	
Interface		
Video Input	8*BNC	
Video Output	1*VGA,1*HDMI	
Audio I/O	1/1	
Alarm I/O	--	
Ethernet	1*10/100Mbps Ethernet port, RJ45 port	
PTZ Control	--	
USB	2*USB2.0	
Max HDD	1x8TB	
General		
Intelligent Video	Tripwire, Intrusion, Abandoned, Missing Object, Scene change detection, Human detect	
Temperature	0 ℃ - + 55 ℃	
Power	12V/2A	
Consumption	<15W(Without HDD)	
Dimension	255mm(L)*236mm(W)*44mm(H)	

JF TECH Co.,Ltd.

Headquarters(Hangzhou):

Building 9, Yinhu Innovation Center, Hangzhou, China

Business Center(Shenzhen):

A 7th Floor, Block Sakata 5 Avenue and Chong Hing Times Tower Shenzhen

All Rights Reserved • Specifications subject to change without notice.

Website:<http://www.jftech.com>

Tel:+86-0571-23271188

Tel:+86-0755-32898088