

JF-ADVR-F8132

32ch Fribrid 1080N 4HDD ADVR



Features

- ◆ Up to 4M-N@8fps,5M-N@6fps
- ◆ Support XVI/AHD/TVI/CVI/ CVBS/IP Self-adaptive
- ◆ Support Intelligent Functions
- ◆ Support D/A Conversion(Free combination of Analog and IP in pure Analog mode)
- ◆ HDMI/VGA Simultaneous Video Output
- ◆ Support DHCP,FTP,DNS,DDNS,NTP,UPNP,EMAIL,3G,WIFI
- ◆ Support ONVIF Protocol
- ◆ Support WEB,VMS,MYEYE Platform
- ◆ Support Mobile Phone Monitoring(IOS ,Android)
- ◆ Cloud Services,P2P,Alarm Information Push To Phone
- ◆ Support Multi-Language

Dimensions



JF-ADVR-F8132

32ch Fribrid 1080N 4HDD ADVR

Specification

| 4HDD | | |
|-------------------|--|----------------------------|
| Model | JF-ADVR-F8132 | |
| Video | | |
| Encode | 32*5M-N@6fps/32*4M-N@8fps/32*1080P@8fps/32*1080N@15fps | |
| Playback | 32*5M-N@6fps/32*4M-N@8fps/32*1080P@8fps/32*1080N@15fps | |
| Multi-Mode | Analog | 32*5M-N/32*4M-N/32*1080N |
| | Hybrid | 8*1080N(Analog)+8*960P(IP) |
| | IP | 32*1080P/16*3M/8*5M |
| Video Compression | H.265/H.265+/ H.264/H.264+ | |
| Audio | | |
| Compression | G.711A | |
| Interface | | |
| Video Input | 32*BNC | |
| Video Output | 1*VGA,1*HDMI | |
| Audio I/O | 16/1 | |
| Alarm I/O | 16/4 | |
| Ethernet | 1*10/100/1000Mbps Ethernet port, RJ45 port | |
| PTZ Control | 1*RS485, 1*RS232, Support for multiple PTZ protocol | |
| USB | 2*USB2.0 | |
| Max HDD | 4*8TB | |
| General | | |
| Intelligent Video | Tripwire, Intrusion, Abandoned,Missing Object,Scene change detection,Human detect | |
| Temperature | 0 °C - +55 °C | |
| Power | 12V/6A | |
| Consumption | <15W(Without HDD) | |
| Dimension | 440mm(L)*400.5mm(W)*60mm(H) | |

JF TECH Co.,Ltd.

Headquarters(Hangzhou):

Building 9, Yinhu Innovation Center, Hangzhou, China

Business Center(Shenzhen):

A 7th Floor, Block Sakata 5 Avenue and Chong Hing Times Tower Shenzhen

All Rights Reserved • Specifications subject to change without notice.

Website:<http://www.jftech.com>

Tel:+86-0571-23271188

Tel:+86-0755-32898088