

# JF-VS-7116C-E


## 16 HDD Storage Server



## Features

- ◆ Manage platform software professionally
- ◆ High-performance processor
- ◆ System information real-time backup
- ◆ Multi-functional integration
- ◆ Multi-level server cluster, cascade
- ◆ User-friendly operation and maintenance interface
- ◆ High-performance streaming data management structure;
- ◆ Simple open architecture
- ◆ Advanced network transmission
- ◆ Adapt to a variety of architectures
- ◆ Alarm management and video collaboration
- ◆ Rich video applications
- ◆ Testing equipment operating status
- ◆ Perfect log management
- ◆ CPU Smart FM
- ◆ Intelligent fan speed control fine
- ◆ Intelligent drive hibernation
- ◆ Remote server configuration
- ◆ Memory self-starting function
- ◆ Density chassis design

## Dimensions



# JF-VS-7116C-E

## 16 HDD Storage Server

### Specification

Model	JF-VS7116C-E
<b>Performance</b>	
Video (2Mbps)	200-CH Management+200-CH-Recording+64-CH Forwarding
<b>System Parameters</b>	
Main Processor	64 Bit Multi-Core Processor
Operation System	LINUX Operation System
<b>Disk</b>	
System Disk	120GB/SSD
Hard Disk	16*SATA (Maximum support single disk 8TB)
Installation	Independent disk bracket, Support SATA 3Gb/s,6.0Gb/s
RAID Mode	Hardware-level Raid0, 1, 5, 6, 10, 50, 60 , support global and dedicated hot spare parts
<b>External Interface</b>	
Network Interface	2*10/100/1000 Adaptive RJ45 Interface, 1*IPMI 2.0 Remote Management RJ45 Interface
USB Interface	6 *USB ( 2 *Preposition+6* Backplane )
Communication parallel port	1*RS232
Display Interface	1*VGA
<b>Panel</b>	
Button	Power switch, restart button
LED Indicator	Front-end: 1 *power indicator, 2 *network indicator. 1 *built-in disk indicator 1 *built-in fan indicator Back-end: 2 *network lights, Bracket: 2* disk status lights
<b>External Interface</b>	
Power Supply	600W single Power Supply
Voltage Input	AC100V~240V, 50Hz~60Hz
Working Temperature	Working: 5℃~40℃ Storage: -20℃~70℃
Working Humidity	Working: 20%~80%RH ( No Ice、 No Condensation ) Storage: 5%~95%RH ( No Ice、 No Condensation )
Case	3U standard
Dimension(mm)	437.5mm(width)x650(depth)x133mm(height)